

# Aqualoo Bersa A Partition System

## Toilet Partitions in the Bersa A Cubicle System

- Available only in 13mm Compact Laminate.
- Overall height is 2700mm maximum floor to ceiling.
- Division Panel: Floor to ceiling panel to a max. of 2700mm high x 1500 - 1800mm deep.
- Frontal Panels: 2700mm maximum height. Minimum width 150mm, varying to suit room dimensions.
- End Nibs: 2700mm high. Minimum width 70mm, varying to suit room dimensions.
- Doors: 1700mm high x 600mm wide with a 20mm floor clearance 50mm clearance to overhead panel. Ambulant doors require a 700mm clearance opening as per AS1428.1-2009.
- Panels above door: to be Biscuit Joined to Frontals and End Nibs, and secured to ceiling with U channel, optional ventilation slits 5mm wide
- Headrail: Extruded Anodised Aluminium U Section headrail.
- Wall Channels: Extruded Anodised Aluminium U Section.
- Floor Mounted pinned directly to the floor.
- Fittings: All hinges, indicator, turn snib and coat hook to be the Aqualoo Aqualock concealed series. (Each Hardware Kit includes a coat hook with bumper.)
- Fixings: All screws to be 304 stainless steel.
- Refer to the Finishing Schedule for the colour scheme.

## Shower Partitions in the Bersa A Cubicle Systems as per above and include the following:

- Available only in 13mm Compact Laminate.
- Standard Partition Depth: 1800mm.
- Nib Wall/Splash Panel: 1905mm high including a 205mm floor clearance, 295mm wide floor mounted on an anodised aluminium AQ adjustable pedestal foot. Secured to the side wall/division with an Extruded Anodised Aluminium U Section.
- Seat/Bench: Approx. 290mm wide x 890mm long, varying to suit project dimensions. Supported by 40mm x 40mm Extruded Angle Section on three sides.
- Hooks: Each cubicle includes 2 hooks positioned above the Seat/Bench.

