

# Aqualoo Kindy Partition System

## Specification Guide

### Toilet Partitions in the Kindy Cubicle System

- Available in either 13mm Compact Laminate or 18mm Structural Board.
- Overall height is 1250-1500mm maximum height including a 205mm floor clearance.
- Division Panel: 1250 mm high x 1500-1800mm deep, with a 205mm floor clearance
- Frontal Panels: 1250-1500mm maximum height. Minimum width 150mm, varying to suit room dimensions.
- End Nibs: 1250-1500mm maximum height including a 205mm floor clearance. Minimum width 100mm, varying to suit room dimensions.
- Doors: 1145mm high x 600mm wide with a 205mm floor clearance. Ambulant doors require a 700mm clearance opening as per AS1428.1-2009.
- No Headrail.
- Wall Channels: Extruded Anodised Aluminium U Section.
- Support foot: Anodized Aluminium Proprietary Liberty floor bracket.
- Fittings: All hinges, indicator, turn snib and coat hook to be the Aqualoo Aqualock concealed series. (Each Hardware Kit includes a coat hook with bumper.)
- Fixings: All screws to be 304 stainless steel.
- Refer to the Finishing Schedule for the colour scheme.

### Shower Partitions in the Kindy Cubicle Systems as per above and include the following:

- Available only in 13mm Compact Laminate.
- Standard Partition Depth: 1800mm.
- Nib Wall/Splash Panel: 1250-1500mm maximum height including a 205mm floor clearance, 295mm wide. Secured to the side wall/division with an Extruded Anodised Aluminium U Section.
- Seat/Bench: Approx. 290mm wide x 890mm long, varying to suit project dimensions. Supported by 40mm x 40mm Extruded Angle Section on three sides.
- Hooks: Each cubicle includes 2 hooks positioned above the Seat/Bench.

- Fixings: All screws to be 304 stainless steel.
- Refer to finishing Schedule for colour scheme