

# Aqualoo Contemporary Partitions System

## Toilet Partitions in the Contemporary Cubicle System

- Available in either 13mm Compact Laminate or 18mm Structural MR MDF Board.
- Overall height: 2027mm including a 205mm floor clearance.
- Division Panel: 1700mm high x 1500-1800mm deep, with a 205mm floor clearance.
- Frontal Panels: 2027mm high including a 205mm floor clearance. Minimum width 150mm, varying to suit room dimensions.
- End Nibs: 2027mm high including a 205mm floor clearance. Minimum width 70mm, varying to suit room dimensions.
- Doors: 1700mm high x 600mm wide with a 205mm floor clearance. Ambulant doors require a 700mm clearance opening as per AS1428.1-2009.
- Headrail: Extruded Anodised Aluminium Round headrail.
- Wall Channels: Extruded Anodised Aluminium U Section.
- Support foot: Anodised Aluminium AQ adjustable pedestal foot.
- Fittings: All hinges, indicator, turn snib and coat hook to be the Aqualoo Aqualock concealed series.
- (Each Hardware Kit includes a coat hook with bumper.)
- Fixings: All screws to be 304 stainless steel.
- Refer to the Finishing Schedule for the colour scheme.

## Shower Partitions in the Contemporary Cubicle Systems as per above and include the following:

- Available only in 13mm Compact Laminate.
- Standard Partition Depth: 1800mm.
- Splash Nib: 1905mm high including a 205mm floor clearance, 295mm wide, mounted on an Anodised Aluminium AQ adjustable pedestal foot. Secured to the side wall/division with an Extruded Anodised Aluminium U Section.
- Shower Seat: Approx. 290mm wide x 890mm long, varying to suit project dimensions. Supported by 40mm x 40mm Extruded Angle Section on three sides.
- Hooks: Each Shower cubicle includes 2 hooks positioned above the Seat.

