## **Aqualoo Pinnacle Partition System**

## **Toilet Partitions in the Pinnacle Cubicle System**

- Available in either 13mm Compact Laminate or 18mm Structural MR MDF Board.
- Overall height is 2027mm including a 205mm floor clearance.
- Division Panel: 1700mm high x 1500 1800mm deep, with a 205mm floor clearance.
- Frontal Panels: 2027mm high. Minimum width 150mm, varying to suit room dimensions.
- End Nibs: 2027mm high. Minimum width 70mm, varying to suit room dimensions.
- Doors: 1700mm high x 600mm wide with a 205mm floor clearance. Ambulant doors require a 700mm clearance opening as per AS1428.1-2009.
- Headrail: Anodised Aluminium Round headrail.
- Wall Channels: Extruded Anodised Aluminium U Section.
- Support foot: Anodised Aluminium Proprietary Liberty floor bracket.
- Fittings: All hinges, indicator, turn snib and coat hook to be the Aqualoo Aqualock concealed series. (Each Hardware Kit includes a coat hook with bumper.)
- Fixings: All screws to be 304 stainless steel.
- Refer to the Finishing Schedule for the colour scheme.

## Shower Partitions in the Pinnacle Cubicle Systems as per above and include the following:

- Available only in 13mm Compact Laminate.
- Standard Partition Depth: 1800mm.
- Nib Wall/Splash Panel: 1905mm high with a 205mm floor clearance, 295mm wide floor mounted on an anodized aluminium AQ adjustable pedestal foot. Secured to the side wall/division with an extruded anodised aluminium U section.
- Seat/Bench: Approx. 290mm wide x 890mm long, varying to suit project dimensions. Supported by 40mm x 40mm extruded angle section on three sides.
- Hooks: Each cubicle includes 2 hooks positioned above the seat/bench.

