

CAPITAL

TOILET PARTITIONS

Toilet partitions in the Capital Cubicle System available in both 13mm Compact Laminate and 18mm MR Board. Shower partitions available in 13mm Compact Laminate only.

- Overall Height:** To match ceiling height.
- Overall Depth:** 1500mm to 1800mm.
- Frontal Panels:** Floor to ceiling including 100mm floor clearance, minimum width 250mm.
- End Nibs:** 2700mm high or a nominal ceiling height including 100mm floor clearance. Minimum width 70mm, varying to suit room dimensions, maximum 450mm.
- Doors:** 1800mm high x 600mm wide with 100mm floor clearance. Ambulant doors require a 700mm clearance opening as per AS1428.1-2009. Privacy profile option available.
- Door Hardware:** Aqua Series door hardware available in satin chrome or satin matte black finish. Door hardware kit includes indicator, lockset, bumper, lift off spring hinges and coat hook. Bolt through option available.
- Fittings:** Ceiling fixing detail - Frontal panels attached to the ceiling via locating pins. Pedestal - Offset clear anodised aluminium foot. Wall channels - Clear anodised aluminium U channel. Powdercoating option available.
- Fixings:** All in 304 stainless steel.
- Colour Selection:** Refer to the Finishing Schedule for the colour scheme.

SHOWER PARTITIONS

Shower partitions in the Capital Cubicle System available only in 13mm Compact Laminate, as per above and include the following:

- Standard Depth:** 1800mm.
- Splash Nib:** 1800mm high with 100mm floor clearance, 295mm wide, mounted on a clear anodised aluminium foot with black nylon base option available. Secured to the side wall/division with clear anodised aluminium U channel.
- Shower Seat:** Approx. 290mm wide x 890mm long, varying to suit project dimensions. Supported by 40mm x 40mm extruded Angle Section on three sides.
- Hooks:** Each Shower cubicle includes 2 hooks positioned above the Seat.
- Options:** Divisional Panels - fix panel to the floor scalloped back 200mm from frontal, remove 80mm clear anodised aluminium foot. Floor clearance - increase to 205mm, use 205mm support feet in place of 80mm clear anodised aluminium foot.

CAPITAL

OFFSET PEDESTAL FOOT / CEILING MOUNTED

